



Data Sheet

3M™ Volition™ Punch Down RJ45 Panels Category 5e and Category 6



Easy-to-use punch down panels which offer 24 ports in 1U, ideal for reliable, fast installation.

The panels have a removable rear cable manager for cable strain relief and correct guiding of cables to the point of termination.

The panels are available in either Category 5e UTP or Category 6 UTP. Rounded edges on the front plate provide an aesthetic appearance and improved mechanical strength.

A full fixing kit is provided and wires can be punched down with either LSA or 110 tools.

Panels have post numbering and space for individual port labelling.

The panels are available in black.

Features

- T568A or T568B wiring
- Terminates with LSA or 110 tools
- Fully shuttered presentation when loaded
- Removable cable retention bar

Benefits

- ... universal application
- ... widely available tool used for assembly
- ... increased dust protection, especially during installation or in a dirty environment
- ... simplifies punch down, gives cable strain relief, controls cable bending and increased system performance

Specifications

Electrical performance	Category 5e panels meet TIA/EIA-568-B.1 Category 5e link standard and ISO/IEC 11801 and EN 50173-1 Class D performance Category 6 panels meet TIA/EIA-568-B.2.1 Category 6 link standard and ISO/IEC 11801 and EN 50173-1 Class E performance
Storage temperature	-40° to +70°C
Operating temperature	-10° to +60°C
Humidity	Max 93% (non condensing)
Colour	Black

Ordering information

24 port Category 5e Punch Down Patch Panel
24 port Category 6 Punch Down Patch Panel

Ref No

VOL-PD-CAT5E-24P
VOL-PD-CAT6-24P



Important Notice: 3M does not accept responsibility or liability, direct or consequential arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable

to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price of the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.



3M Headquarters

3M United Kingdom PLC
3M Centre
Cain Road
Bracknell
Berkshire, RG12 8HT

3M Customer Contact Centre

3M Telecommunications
3M United Kingdom PLC
Tel: 0870 609 4639
Email: 3Melectrouk@mmm.com
www.3M.co.uk/telecommunications

3M and Volition are trademarks of the 3M Company.
Please recycle. Printed in UK. © 3M 2010.
All rights reserved to make technical alterations.
25.03.2010

