



Epson EB-1960

Ultra Bright, Easy Setup. Amazing Performance.

Ultra Bright – 5,000 Lumens Light/Colour light output in a compact, light weight unit

Broad Connectivity – HDMI, DisplayPort, USB display, USB Slideshow, and network connectivity

Advanced Networking Capability – Enables users to monitor, control and present from a remote location

Enhanced Image Quality – Featuring the Faroudja DCDi Cinema chip and DICOM SIM mode the EB-1960 produces images with fine detail, sharpness and smooth motion

Rich Functionality – With a range of easy to use functions such as Epson iProjection, Multi PC and PC Free Projection the EB-1960 creates more engaging and captivating meetings

Easy installation and Setup – Making use of the Vertical and Horizontal keystone correction, it is not necessary to place the projector in the centre of the desk

Epson EB-1960



Product Specifications

PRODUCT NAME	Epson EB-1960
PRODUCT CODE	V11H473053
WHAT'S IN THE BOX	EB-1960 Projector, 1.8m Computer Cable, 1.8m power cable, Remote Control, Batteries, Projector Software Ver. 1.20d (CD ROM), Password Protect Sticker, Manual
TECHNOLOGY	
Projection System	Epson 3LCD, 3-chip technology
LCD Panel	0.63-inch with MLA
OPTICAL	
Zoom	1-1.6 (Optical Zoom)
Screen Size	30" to 300" [0.84 to 8.4 m] (Zoom: Wide) 30" to 300" [1.36 to 13.9 m] (Zoom: Tele)
Projection Distance	60" screen 1.69 - 2.75 m
Throw Ratio	1.38 (Zoom: Wide), 2.24 (Zoom: Tele)
Projection Lens F Number	1.51-1.99
Projection Lens Focal Length	18.2mm-29.2mm
Focus Method	Manual Focus
Offset	8.6:1
IMAGE	
Colour Light Output	5,000 Lumens
White Light Output	5,000 Lumens
Resolution	XGA
Native Aspect Ratio	4:3
Contrast Ratio	3,000:1
Lamp Hours	Normal/Eco: 2,500/4,000 Hours
Lamp Type	245 W UHE (E-TORL)
Keystone Correction Vertical:	-30 to +30 degrees
Keystone Correction Horizontal:	-30 to +30 degrees

CONNECTIVITY	
Input: Video	1 x RCA (Yellow), 2 x Component (via D-sub 15-pin)
Input: Computer	2 x D-sub 15-Pin (RGB), 1 x USB 2.0 type B
Input: USB Memory Device	1 x USB Type A Ver.2.0
Input: Three-In-One USB Display	1 x USB 2.0 type B
Input: Digital	1 x HDMI, 1 x Displayport
Input: Audio	1 x RCA (Red/White), 2 x Stereo mini jack
Input: Control	1 x USB 2.0 type B, 1 x RS232C
Input: Epson USB Document Camera	1 x USB 2.0 type B
Network I/O	1 x RJ45 (100Mbps)
Wireless Connectivity	N/A
Output: Video	1 x D-sub 15 pin (black moulding)
Output: Audio	1 x Stereo mini jack
Speaker Output	10W
ADVANCED FEATURES	
EasyMP Network & Control	Yes
EasyMP Network Projection	Yes
PC Free Presentations	Yes
USB Plug 'n Play	Yes
AV Mute Slide	Yes
Instant Off	Yes
Direct Power On/Off	Yes
Security	Padlock & Security Cable Hole Kensington®-style lock provision Wireless LAN Unit Lock Password protect function
Colour Modes	Dynamic, Presentation, Theatre, Photo, sRGB, Blackboard, Whiteboard, DICOM.SIM
GENERAL	
Dimensions D x W x H (excluding feet)	271 x 377 x 108mm
Weight	3.7kg
Lamp Warranty	12 months or 750 hours - whichever comes first
Projector Warranty	3 years
Power Consumption: Lamp on	Normal/Eco: 377/250W
Power Consumption: Standby	0.44W (communication off)
Noise Level	Normal/Eco: 37/29dB



Better Products for a Better Future

EPSON
EXCEED YOUR VISION

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA
3 Talavera Road
North Ryde NSW 2113
Tel: (02) 8899 3666
www.epson.com.au

EPSON NEW ZEALAND
Level 2, 7-9 Fanshawe Street
Auckland, 1010
Tel: (09) 366 6855
www.epson.co.nz

ABN 91 002 625 783
7/12