

## Speedlight SB-N5

Control your direction of light. This flash easily attaches to the multi-accessory port on the Nikon 1 V1 camera to produce beautiful, natural-looking images. Powered via the camera, it needs no batteries and boasts a capture illuminator LED light on the front of the unit to ensure steady light when using Motion Snapshot or Smart Photo Selector in the dark.



### Key Features

Electronic construction	Automatic Insulated Gate Bipolar Transistor (IGBT) and series circuitry
Supported cameras	Interchangeable lens format cameras with multi accessory ports
Guide number (20 °C/68 °F)	8.5/27.9 (ISO 100, m/ft), 12/39.4 (ISO 200, m/ft)
Effective flash range (i-TTL)	0.6 m to 20 m/2 ft to 66 ft (varies with ISO sensitivity, bounce angle, and aperture)
Supported flash control modes	i-TTL, manual
Options available using camera controls	Flash mode: Fill flash (front-curtain sync), front-curtain with slow sync, rear-curtain sync, and rear-curtain with slow sync Flash control mode: i-TTL, manual Flash compensation
Bounce angle	Vertical: Flash can be rotated up 90°; from horizontal with stops where the flash is pointing directly ahead and at 60°, 75°, and 90°; Horizontal: 180°; right to 180°; left, with stops where the flash is pointing directly ahead and at 30°, 60°, 75°, 90°, 120°, 150°, and 180°;
Device on/off	Power switch used to turn SB-N5 on and off
Flash status indicator	Lights when charging is complete Warning indicator: Blinks (see the camera Reference Manual for more information)
Capture illuminator	When SB-N5 is used with compatible cameras, lights for about six seconds during buffering in Smart Photo Selector and Motion Snapshot modes
Capture-illuminator status indicator	Lights to show that capture illuminator can be used
Flash duration	Lights for about 1/4000 s when fired at full power

Other options	Thermal cut-out Firmware can be updated from camera
Dimensions (W x H x D)	Approx. 50 x 70.5 x 40.5 mm/2.0 x 2.8 x 1.6 in.
Weight	Approx. 70 g/2.5 oz (SB-N5 only)
Supplied accessories	Soft case SS-N5, Mounting foot cover BS-N2000