

Wireless Speedlight Commander SU-800



Main Features

When using i-TTL compatible Nikon digital SLR cameras and Speedlight, user can divide the Speedlight units into three groups and control the flash output independently for each group

- Features a Commander function that can trigger wireless remote flash (SB-900, SB-800, SB-600, or SB-R200) units without a master flash unit.
- One-touch switching between close-up and Commander modes
- Easy-to-use close-up flash operations. Two types of operations: Dual-light close-up flash and Triple-light close-up flash
- Easy-to-view LCD panel
- Compact and lightweight
- Soft Case SS-SU800 (supplied)
- When using the SU-800 with cameras not compatible with i-TTL flash control, only close-up flash operation (using cords) is possible in use with the optional TTL Cord SC-30.

Specifications

Transmission mode	Infrared-pulse emitting communication using a flash discharge tube
Transmission range	Approx. 20m (66 ft.) for SB-800/SB-600; Approx 4m (13 ft.) for SB-R200 at normal settings
Number of channels	4
Number of groups	3
Number of transmissions per battery	Approx. 1200
Transmission interval	Approx. 1 second
Flash light wavelength	Approx. 800 to 1000nm (infrared ray)
Flash coverage	Approx. 60°
Display	LCD, ready-light

AF-Assist Illuminator

Approx. 10m (33 ft.) at center area using a 50mm f/1.8 lens

Power source

One CR123A (3V) lithium battery

Weight (without battery)

Approx. 160g (5.6 oz.)

Dimensions (W x H x D)

Approx. 68 x 96 x 58mm (2.7 x 3.8 x 2.3 in.)

Included accessories

Soft Case (SS-SU800)

Optional accessory

TTL Cord (SC-30)