



PANASONIC

CORDED IP PHONE

KX-HDV130

DISPLAY

LCD Display	Monochrome Graphical
LCD Size	132 × 64 pixel 2.3 inch Graphical LCD
LCD Contrast	6 levels
LCD Backlight	On/Auto/Off
Desk Mount Tilt	Install Options
Wall Mount	Yes – 2 positions
Power Adaptor	KX-A440 (optional)
	KX-A423 (optional)

AUDIO FEATURES

Handset, Speaker, Headset	8 levels (includes echo cancellation and distortion prevention)
Volume	27
Ringtones	8 levels + Off
Ringer Volume	RJ9 jack
Headset Port	-
Electronic Hook Switch Control	G.711a-law / G.711μ-law / G.722 (wideband) / G.729a
Port	Yes
Audio Codec	Yes
HD Voice	Yes
Speaker Phone	

KEYS

Programmable Keys	2
Phone Book (Local)	Software Features
LDAP Remote Phonebook	500
XML Remote Phonebook	Yes
Call Log Entries	Yes
Conferencing	30 incoming calls + 30 outgoing calls
XML Application	3 parties (within terminal – multi-party dependent on server)
Music on Hold	Yes
	Supplied by Host Service (PBX / SIP Server)

IP FEATURES

SIP Accounts	2
SIP Compatibility	RFC 3261 Standard SIP Server, Asterisk, Broadsoft, Panasonic IP PBX
IP Version	IPv6 / IPv4
DHCP Client	Yes
DNS	Yes
HTTP	Yes
HTTPS	Yes
SNTP Client	Yes
VLAN (802.1q)	Yes
QoS (DiffServ)	Yes

CONFIGURATION

Plug & Play Configuration	Server based configuration, TR-069
Manual Configuration	Internal web Configurator, Local (LCD based) network configuration

INTERFACE

Ethernet Ports	2
Ethernet Interface	10/100 Mbps
PoE (Power over Ethernet)	Yes

OTHERS

	PoE
	Stand-by: approx. 2.2 W (ECO mode off), 1.9 W (ECO mode on)
	Talking: 2.3 W (ECO mode off), 2.0 W (ECO mode on)
	Max: 2.8 W
Power Consumption	AC Adaptor
	Stand-by: 2.0 W (ECO mode off), 1.3 W (ECO mode on)
	Talking: 2.1 W (ECO mode off), 1.4 W (ECO mode on)
	Max: 2.8 W
Operating Environment	0 °C - 40 °C (32 °F - 104 °F)
Dimensions (Width x Depth x Height; excluding the handset, stand attached)	High position: 167 mm x 165 mm x 148 mm Low position: 167 mm x 173 mm x 115 mm
Weight (with handset,handset cord and stand)	691 g