

Megapixel HD PoE Dome Network Camera

- **Camera**
- **General**
 - Sensor: 1/4" Megapixel CMOS sensor
 - Max. Resolution: 1280 x 1024 pixels
 - Board Lens
 - Focal Length: 3.58 mm
 - Aperture (F/No): F2.0 +/- 5%
 - Minimum illumination: 1 Lux
 - Viewing angle:
 - Horizontal: 63°
 - Vertical: 46°
 - Diagonal: 74°
- **Audio**
 - Microphone output (microphone sold separately)
 - Audio output: Mono (speakers sold separately)
 - Sensitivity: -42 dB +/- 3 dB
 - Frequency: 100~10,000 Hz
 - S/N: 65 dB
 - Format: PCM/AMR

- **Pan/Tilt (Manually)**
 - Manually adjust camera to final fixed position
 - Pan: -175° ~ +175°
 - Tilt: 20° ~ 90°
- **SD Slot**
 - Supports SD/SDHC (up to 32 GB)
- **Hardware**
- **Network**
 - IEEE 802.3u 10/100 Mbps Fast Ethernet
 - IEEE 802.3af PoE
- **LED**
 - Power, Link/Act (can turn off LEDs)
- **Reset Button**
 - Reboot or restore to factory default
- **Power Consumption**
 - 7 Watts max
- **Power**
 - Input: 100 ~ 240V AC , 0.5A, 50~60Hz
 - Output: 12VDC 1.5A external power adapter (for non-PoE installations)

- **Dimension**

- 131 x 131 x 127 mm (5.2 x 5.2 x 5 in.)

- **Weight**

- 570 g (20.1 oz.)

- **Temperature**

- Operating: 0°C ~ 50°C (32°F ~ 122°F)
- Storage: -15°C ~ 60°C (5°F ~ 140°F)

- **Humidity**

- Max 90% (non-condensing)

- **Certifications**

- CE, FCC

- **Requirement**

- **Management Interface**

- Internet Explorer 6.0 or above

- **To Run TRENDnetVIEW**

- Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit)
- Windows Server 2003, 2008

- **TRENDnetVIEW**

- Channel: supports up to 32 cameras
- Record/Playback/Motion Detection/Audio

- **Network Protocols**
 - TCP/IP, IPv4, IPv6, UDP, ICMP
 - DHCP client, NTP client, DNS client, DDNS client, SMTP client, FTP client
 - HTTP, HTTPS
 - Samba client
 - PPPoE
 - UPnP
 - Bonjour
 - RTP (Real Time Protocol)
 - RTSP (Real Time Streaming Protocol)
 - RTCP (Real Time Control Protocol)
 - SSL
 - ONVIF
 - 3GPP (video only)
- **Management**
- **Remote**
 - Remote management supported
- **Backup/Restore**
 - Save/retrieve configuration files
- **Settings**

- **Image**
 - Automatic exposure, white balance, and gain control
 - Brightness, saturation, sharpness, light frequency, and mirror (horizontal/vertical)
- **Video**
 - Encoding type: H.264, MPEG-4, MJPEG
 - Compression: 5 levels
 - Resolution/Frame Rate: SXGA (1280 x 1024) up to 15fps
 - 720p (1280 x 720) up to 20fps
 - VGA (640x480) up to 30fps
 - QVGA (320x240) up to 30fps
 - QQVGA (160x120) up to 30fps
 - Multi-Stream: H.264: SXGA, VGA, QVGA, QQVGA, 720P
 - MPEG-4: VGA, QVGA, QQVGA
 - MJPEG: SXGA, VGA, QVGA, QQVGA, 720P
- **Recording/snapshot**
 - Recording type: continuous, schedule, motion detection, or snapshot
 - Event Management
 - Event trigger: motion, schedule
 - Store video file to SD card or storage device
 - Send Instant message to Jabber client via Jabber server

- **Overlay**
 - Text overlay: time, date, and text
 - Mask overlay: define up to 2 opaque boxes to conceal portions of the recording area
- **QoS**
 - DSCP
- **Port Settings**
 - HTTP port: 80 (default)
 - RTSP port: 554 (default)
- **Digital Zoom**
 - 3x
- **Dynamic DNS**
 - Yes
- **Time**
 - Synchronize with NTP server or set time/date manually
- **Email**
 - Supports up to 2 destination accounts
- **System Log**
 - 100 entries (max.)

Package Contents

- TV-IP262P
- Multi-language Quick Installation Guide
- CD-ROM (Utility, Software, & User's Guide)
- Power adapter (12 V DC, 1.5 A)
- Network cable (1.5 m / 5 ft.)
- Camera mounting Kit