

# Outdoor Megapixel HD PoE Day/Night Internet Camera

- **Lens**
  - Focal Length: 4.2 mm, F1.6
  - Board Lens
  - Sensor: ¼" Megapixel CMOS sensor
  - Zoom: Digital 4x
- **Viewing Angle**
  - Diagonal: 62.9°
  - Horizontal: 53.1°
  - Vertical: 33.7°
- **Minimum Illumination**
  - IR off: 0.5 lux
  - IR on: 0 lux
  - 15 meters IR illumination distance
- **Video Codecs/Resolution**
  - H.264: 1280 x 800 up to 30 fps
  - MPEG4: 1280 x 800 up to 30 fps
  - JPEG: 1280 x 800 up to 30 fps
- **Audio**
  - External microphone port
  - External speaker port
- **Standard**

- IEEE 802.3u
- IEEE 802.3af
- **Device Interface**
  - 10/100 Mbps PoE Port
  - LED indicator
  - BNC port
  - Microphone jack
  - Speaker jack
  - GPIO terminal
  - Power jack (optional)
- **Network Protocol**
  - IPv4, IPv6, UDP, TCP/IP
  - DHCP client, NTP client, DDNS client, SMTP client, FTP client
  - SNMP, QoS/DSCP, IEEE 802.1X
  - Samba, Bonjour
  - HTTP, HTTPS
  - PPPoE
  - UPnP, RTSP, RTP 3GPP
- **Dimension**
  - Camera: 92 x 62 mm (3.62 x 2.44 in.)
  - Weight: 450 g (without bracket); 535 g (with bracket)
- **Operating Temperature**
  - -20 - 50°C (-4 - 122°F)
- **Humidity**

- Max. 90% non-condensing
- **Power**
  - Input: 100 - 240 V AC , 1 A, 50 - 60 Hz
  - Output: 12 V DC 1 A external power adapter (for non-PoE installations)
  - Max. consumption: 6.24 W
- **Management Interface**
  - Image setting: brightness, contrast, hue, saturation, sharpness, Auto Gain Control, shutter time, sens-up, Digital WDR, day & night light sensor, flip, mirror, 90 degree rotation
  - Recording: event based, motion detection recording to email, FTP, GPIO trigger and Samba, Scheduled recording to email, FTP and Samba
  - Snapshot: Trigger event (motion detection), Send alert to email, FTP and/or Samba, Real time snapshot
  - Management Setting: Maximum 22 user accounts, Supports remote management
  - Compatibility: Internet Explorer 8.0 or higher, Firefox® 12.0 or higher, Chrome™ 19.0 or higher, Safari® 4 or higher
- **Camera Software: TRENDnetVIEW Pro**
  - Supports up to 32 cameras
  - Multiple language support
  - Set recording options (motion detection, schedule, event trigger)
  - Search and playback
  - Custom viewing modes and options

- Compatibility: Windows® 8, 7, Vista, XP, Windows Server® 2003, 2008
- **TRENDnetVIEW Mobile App**
  - View your camera from your portable device
  - Take snapshots
  - Zoom in & out
  - 2 way audio
  - Compatibility: IOS and Android™
- **Warranty**
  - 3 year limited

## **Package Contents**

- TV-IP302PI
- Multi Language Quick Installation Guide
- CD-ROM (Utility, Software, & User's Guide)
- Power adapter (12 V DC, 1A)
- Network cable (1.5 m/5 ft.)
- RJ45 coupler
- Camera mounting hardware