

Megapixel HD PoE Internet Camera

- **Camera**
- **General**
 - Sensor: 1/4" CMOS Sensor
 - Board Lens
 - Focal Length: 4 mm
 - F/No: 1.5
 - Minimum illumination: 1 lux
 - Focus Depth: 20 cm ~ infinity
 - View:
 - Horizontal: 51.8 degrees
 - Vertical: 33.8 degrees
 - Diagonal: 59.6 degrees
 - Digital Zoom: 4x
- **Audio**
 - Built-in omni-directional microphone
 - Sensitivity: -40 dB +/- 3 dB (5 meters max)
 - Frequency: 100~2 Hz
 - S/N: >60 dB

- Codec: PCM / ADPCM
- External speaker output (speaker sold separately)
- Two-way audio with echo canceling
- **Hardware**
 - IEEE 802.3u 10/100 Mbps Auto-MDIX Fast Ethernet
 - IEEE 802.3af Power over Ethernet
- **LED**
 - Power, Link / Act
- **Micro SD slot**
 - Supports Micro SD (SDHC, up to 32 GB)
- **Reset Button**
 - Reset to factory default
- **Power Consumption**
 - Max 3.15 Watts
- **Power**
 - Input: 100~240V, 50/60 Hz, 0.2A
 - Output: 5V, 1.2A external power adapter
- **Dimension**
 - 75 x 115 x 30 mm (2.95 x 4.5 x 1.2 in.)
- **Weight**

- 120 g (4.2 oz.)
- **Temperature**
 - Operating: 0°C ~ 40°C (32°F ~ 104°F)
 - Storage: -25°C ~ 70°C (-13°F ~ 158°F)
- **Humidity**
 - Max 95% (non-condensing)
- **Certifications**
 - CE, FCC
- **Requirement**
- **Management Interface**
 - Internet Explorer 7.0 or above
 - Firefox, Safari, and Chrome
- **To Run software**
 - Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit)
 - Windows Server 2003, 2008
- **TRENDnetVIEW Software**
 - Channel: supports up to 32 cameras
 - Record / Playback / Motion Detection / Audio
- **Network Protocols**
 - IPv4, ARP, TCP, UDP, ICMP

- DHCP Client, NTP Client, DNS Client, DDNS Client, SMTP Client, FTP Client
- HTTP
- Samba Client
- PPPoE
- UPnP
- LLTD
- RTP (Real Time Protocol)
- RTCP (Real Time Control Protocol)
- RTSP (Real Time Streaming Protocol)
- 3GPP
- **Management**
- **System**
- Web based administration
- NIPCA support
- **Access**
- Up to 20 user accounts
- **Backup / Restore**
- Save / retrieve configuration files
- **Log**
- System log up to 500 entries

- **Micro SD**
 - View, download, delete files
 - Format and remove Micro SD card
- **Settings**
- **Image**
 - Brightness, contrast, saturation, sharpness, white balance, flip, mirror (horizontal / vertical), black & white, indoor, outdoor, schedule mode
 - Shutter: 1/3.25s, 1/7.5s, 1/10s, and 1/15s
- **Video Setting**
 - Profile 1: H.264 / MPEG-4
 - Resolution: 1280 x 800, 640 x 400, 320 x 192, 160 x 96
 - Max frame rate: 30fps
 - Profile 2: H.264 / MPEG-4
 - Resolution: 640 x 400, 320 x 192, 160 x 96
 - Max frame rate: 30fps
 - Profile 3: MJPEG
 - Resolution: 1280 x 800, 640 x 400, 320 x 192, 160 x 96
 - Max frame rate: 1280 x 800 @ 5fps, 640 x 400 / 320 x 192 @ 30fps
 - JPEG quality: Low, Fair, Standard, Good, Excellent
 - Profile 4: H.264 / MPEG-4

- Resolution: 640 x 400, 320 x 192, 160 x 96
- Max frame rate: 30fps
- RTSP: http://ipcamera_ip/3gpp
- **3GPP**
 - Video codec: MPEG-4 (no audio support)
 - Protocols: RTSP, RTP
- **Recording**
 - Resolution: Define individual resolution for up to 4 profiles
 - Required storage: 32 MB (minimum per profile)
 - Recording type: event based (motion detection), continuous, and scheduled
- **Event Action**
 - Trigger event: motion detection
 - Action: send real-time snapshot or video recording to FTP or email
- **Port Settings**
 - HTTP port: 80 (default)
 - RTSP port: 554 (default)
- **Time**
 - Synchronize with NTP server or set time / date manually

Package Contents

- TV-IP572P
- CD-ROM (Utility & User's Guide)
- Multi-Language Quick Installation Guide
- Network cable (1.5 m / 5 ft.)
- Power adapter (5V, 1.2A)
- Camera mounting kit